

PTS

3.6Ø x 10 mm

Time-Lag Fuse



Agency Approvals

Agency	Ampere Rating
UL Listed	100mA - 5A

Interrupting Rating

50 amperes at 250V AC

Product Characteristics

Operating Temperature	-55 °C to 125 °C
Material	Body: Ceramic / Caps: Nickel Plated Brass


Electrical Characteristics

Ampere Rating	Opening Time	
	1 In	2 In
	MIN	MAX
100mA to 5A	4 hr	60 sec

Packaging

Packaging Option	Quantity
Bulk	5,000 pcs / box

Mechanical Dimensions (mm)



PTP

3.6Ø x 10 mm

Time-Lag Fuse



Agency Approvals

Agency	Ampere Rating
UL Listed	100mA - 5A
CSA Certified	100mA - 5A

Interrupting Rating

50 amperes at 250V AC

Product Characteristics

Operating Temperature	-55 °C to 125 °C
Material	Body: Ceramic / Caps: Nickel Plated Brass
Leads Wire	Ø0.6 mm 5A and less. Ø0.8 mm for rating above 6A to 7A. Ø1.0 mm for rating above 8A.
Option	* With Heat Shrink Tubing (VM-1) over body * PTP Series Available on Tape & reel

Electrical Characteristics

Ampere Rating	Opening Time	
	1 In	2 In
	MIN	MAX
100mA to 5A	4 hr	60 sec

Packaging

Packaging Option	Quantity
Bulk	500 pcs / box
On Axial Tape & Reel	1,500 pcs / box

Mechanical Dimensions (mm)

